

S p e c i f i c a t i o n

| | |
|-----------------------------------|---|
| Product: | Hot Rubber Melter. |
| Capacity: | 1 Drum - 180 Litres – Approx. |
| Model: | 3 Phase Fully Electric |
| Power: | 415-volt 3 phase – 32 amps (load 20 kW). |
| Plug: | 3 pin female neutral & earth into Melter – 3 pin male neutral & earth into power source. |
| Control Panel: | Digital – Temperature Control. |
| Burner: | Electric heating element. |
| Main Frame: | 40 x 40 x 2mm RHS. |
| Pan: | 5mm plate. |
| End Plates: | Profiled 6mm. |
| Outside Case Sheet: | 2mm. |
| Outlet: | Profiled. |
| Forklift Locating Sleeves: | Channel. |
| Drive: | 415/30/3 phase motor – gearbox. |
| Insulation: | High temperature Rockwool dense slab. |
| Stirrer Shaft: | 40mm BMS. |



Stirrer Shaft

Bearings: 40mm Pillar block.

Casters: 2 No. 200mm fixed
2 No. 200mm swivel/braked.

Lifting Eyebolts: M20 metric collared.
D Shackles: 3.25-ton green pin safety.

Dimensions:

| | |
|------------------------|--------|
| Length: | 1980mm |
| High: | 1560mm |
| Width: | 790mm |
| Loading Height: | 930mm |
| Weight: | 554kg |

This specification and any drawings/images related to it are the sole Copyright of WJ Horrod Ltd and must not be passed to a third party without prior consent.

WJ Horrod Ltd reserves the right to alter, change or modify this equipment to improve it without prior notice.



Image above does not display 1 drum unit and is for reference purposes only.