



S p e c i f i c a t i o n

Product:	Hot Rubber Melter.
Model:	Fully Electric.
Capacity:	270 litres approx.
Power:	415-volt 3 phase – 32 amps (load 20 kW).
Control Panel:	Digital – Temperature Control.
Drive:	415/30/3 phase motor – gearbox.
Plug:	3 pin female neutral & earth into Melter – 3 pin male neutral & earth into power source.
Burner:	Single electric heating element.
Main Frame:	40 x 40 x 2mm RHS.
Pan:	5mm plate.
Stirrer Shaft:	40mm BMS.
Stirrer Shaft Bearings:	40mm Pillar block.
Agitation:	Oscillating continuous paddle.
End Plates:	Profiled 6mm.
Outside Case Sheet:	2mm.



Outlet:	Profiled – 2-piece door and frame.
Forklift Locating Sleeves:	Formed section from 3mm mild steel sheet.
Insulation:	High temperature Rockwool dense slab.
Power Lead:	20 metre 415 volt.
Casters:	2 No. 200mm fixed. 2 No. 200mm swivel/braked. Load capacity 500kg per caster.
Lifting Eyebolts:	M20 metric collared.
D Shackles:	3.25-ton green pin safety.
Dimensions:	Length: 2520mm High: 1520mm Width: 870mm Weight: 687kg

This specification and any drawings/images related to it are the sole Copyright of WJ Horrod Ltd, and must not be passed to a third party without prior consent. WJ Horrod Ltd reserves the right to alter, change or modify this equipment to improve it without prior notice.

74 Years of Excellence
Horrods
Engineering ~ Safety ~ Efficiency



The images shown represent the model, not the capacity approximated in this specification.