



# **S p e c i f i c a t i o n**

<b>Product:</b>	<b>Hot Rubber Melter.</b>
<b>Model:</b>	<b>Fully Electric.</b>
<b>Capacity:</b>	<b>1.5 Drum - 270 Litres approx.</b>
<b>Power:</b>	<b>415-volt 3 phase – 32 amps (load 20 kW).</b>
<b>Control Panel:</b>	<b>Digital – Temperature Control.</b>
<b>Drive:</b>	<b>415/30/3 phase motor – gearbox.</b>
<b>Plug:</b>	<b>3 pin female neutral &amp; earth into Melter – 3 pin male neutral &amp; earth into power source.</b>
<b>Burner:</b>	<b>Single electric heating element.</b>
<b>Main Frame:</b>	<b>40 x 40 x 2mm RHS.</b>
<b>Pan:</b>	<b>5mm plate.</b>
<b>Stirrer Shaft:</b>	<b>40mm BMS.</b>
<b>Stirrer Shaft Bearings:</b>	<b>40mm Pillar block.</b>
<b>Agitation:</b>	<b>Oscillating continuous paddle.</b>
<b>End Plates:</b>	<b>Profiled 6mm.</b>
<b>Outside Case Sheet:</b>	<b>2mm.</b>



<b>Outlet:</b>	<b>Profiled – 2-piece door and frame.</b>
<b>Forklift Locating Sleeves:</b>	<b>Formed section from 3mm mild steel sheet.</b>
<b>Insulation:</b>	<b>High temperature Rockwool dense slab.</b>
<b>Power Lead:</b>	<b>20 metre 415 volt.</b>
<b>Casters:</b>	<b>2 No. 200mm fixed. 2 No. 200mm swivel/braked. Load capacity 500kg per caster.</b>
<b>Lifting Eyebolts:</b>	<b>M20 metric collared.</b>
<b>D Shackles:</b>	<b>3.25-ton green pin safety.</b>
<b>Dimensions:</b>	<b>Length: 2520mm High: 1520mm Width: 870mm Weight: 687kg</b>

**This specification and any drawings/images related to it are the sole Copyright of WJ Horrod Ltd, and must not be passed to a third party without prior consent. WJ Horrod Ltd reserves the right to alter, change or modify this equipment to improve it without prior notice.**



*The images shown represent the model, not the capacity approximated in this specification.*