

## SPECIFICATION

Product: Swift Melt Mastic Asphalt Mixer

Model: 1000kg trailer mounted

Type: Vertical agitation

Capacity: 1000kg

Power: Yanmar L70 low emission electric air cool diesel engine

Drive: Hydraulic forward & reserve mode, tilt with variable speed settings

Construction: Fully welded

Insulation:

Main Body: Outer casing: 2mm mild steel sheet

Inside casing:

Case bottom:

Case ring:

2.5mm mild steel sheet

2mm mild steel sheet

Profile 50 x 8mm

Profile 50 x 10mm

Rockwool dense slab - 50mm thick

Material Pan: Body: 4mm mild steel plate

Bottom: 8mm spun dish mild steel plate

Pan ring: Profile 8mm

Top Plate: Profile 10mm mild steel plate

Lids: Spun mild steel plate

Material Outlet: Profiled ring and door

Burner Trunking: 40 x 40 x 6mm RSA



Stirrer Shaft: 2 ¾" Square bright mild steel

Stirrer Caps: Cast iron

Stirrers: 8mm plate – 80 x 20mm RSF – 50 x 50 x 6mm RSA

Stirrer Shaft

Coupling: 50mm Taper bush

65mm Taper bush

Stirrer Shaft

Bearing: 65mm 4 bolt flange type

Firing: LPG propane gas

Burner: 5" Radial type with pilot protected flame failure system

Thermostat Control: 50-300 Capillary type analogue

Lighting: Bullfinch auto torch

Base Frame: 80 x 40 x 3mm Rectangular hollow section

Charging: Battery – 063 type

Trailer:

Rolling Chassis: Tandem axle

Max Weight: 3500kg

Unladen Weight: 600kg

Body Length: 4000mm

Body Width: 1500mm

Trailer Floor: 4.5mm Aluminum durbar

Cylinders: Double cylinder carrier

1 Leaway off Lea Bridge Road London E10 7QW www.wjhorrod.co.uk ©W J Horrod Ltd 2023



## Overall Sizes with Swift Melt Mixer Mounted:

Weight of Mixer & Trailer: 1480kg

Overall Height: 1980mm

Loading Height: 1370mm

Overall Width: 1930mm

Overall Length: 4052mm

