



S p e c i f i c a t i o n

- Product: Twin Pre-Heater for Thermoplastic.
- Capacity: 15/25/40/50/60 Gallon per heater.
- Heating Type: Direct heat.
- Boiler Construction: Hot rolled prime grade mild steel fully welded, mounted on a common base frame.
- Power: Yanmar air cooled diesel engine fitted with a 12-volt electric key start and charging unit, battery included.
- Drive: Hydraulic Eaton 195cc/reversable motor – group on gear pump 34cc with forward and reverse mode.
- Firing: LPG propane.
- Burners: 5" Radial burners complete with pilot protected flame failure system.
- Temperature Control: 12-volt electrical thermostat with adjustable temperature control which can be set to the required working temperature of the material being used.
- Outlet: Gate type.
- Gas Equipment: 0-2 bar regulator, flashback arrestor and over braided hose.
- Lighting: Detachable Auto-Torch.

As this specification covers all sizes available to order we have not included the weight or dimension of any of the units. We will confirm sizes as requested.

WJ Horrod reserve the right to alter, change and modify this specification to improve the product without prior notice.



www.wjhorrod.co.uk

 **Horrods** 
70 years of engineering excellence



©W J Horrod Ltd



www.wjhorrod.co.uk

1 Leaway off Lea Bridge Road Leyton London E10 7QW T: 020 8539 8746 Email: kim@wjhorrod.co.uk

Company registered in England No. 682155