




S p e c i f i c a t i o n

Product:	Twin Pre-Heater for Thermoplastic.
Capacity:	15/25/40/50/60 Gallon per heater.
Heating Type:	Oil Jacketed.
Boiler Construction:	Hot rolled prime grade mild steel fully welded, mounted on a common base frame.
Pans:	Oil-jacketed – heavy duty construction with 10mm thick plate bottom c/w oil filler plug and expansion tank.
Power:	Yanmar air cooled diesel engine fitted with a 12-volt electric key start and charging unit, battery included.
Drive:	Hydraulic Eaton 195cc/reversable motor – group on gear pump 34cc with forward and reverse mode.
Outlet:	Gate type
Firing:	LPG propane.
Burners:	5” Radial burner complete with pilot protected flame failure system.
Temperature Control:	12-volt electrical thermostat with adjustable temperature control which can be set to the required working temperature of the material being used.
Gas Equipment:	0-2 bar regulator, flashback arrestor and over braided hose.
Lighting:	Detachable Auto Torch.

72 Years of Excellence **Horrods** Engineering ~ Safety ~ Efficiency

As this specification covers all sizes available to order we have not included the weight or dimension of any of the units. We will confirm sizes as requested.

WJ Horrod reserve the right to alter, change and modify this specification to improve the product without prior notice.



1 Leaway off Lea Bridge Road London E10 7QW www.wjhorrod.co.uk

©W J Horrod Ltd 2022