



## S p e c i f i c a t i o n

Product:	Thermostat Control Bitumen Boiler		
Model:	SMS2		
Capacity:	25 & 50 Gallon.		
Mounted On:	Sub-frame fitted with 2 No. 12" solid rubber tyre wheels		
Outside Case:	16-gauge sheet double skin, Rockwool high temperature dense slab insulation between inner and outer skin, profiled end plates and fully welded seams.		
Case Sub Frame:	50 x 25 x 16-gauge ERW 40 x 40 x 3mm RSA		
Removable Pan:	3mm hot rolled sheet fully welded both inside and out.		
Lid:	Full size fully opening		
Burner:	Stainless steel ribbon bar burner c/w pilot.		
Thermostat:	Tempcon 2020 digital thermostat control 12/24V. Flame failure pilot protected main burner via flame failure valve.		
Outlet:	1" Plug cock type – Gate Type		
Firing:	LPG propane gas.		
Dimensions:	25 gallons:	50 gallons:	
	Overall length	Overall length	1620mm
	Overall width	Overall width	770mm
	Overall height	Overall height	945mm
	Weight	Weight	180kg approx.



This specification and any drawings/images related to it are the sole copyright of WJ Horrod Ltd and must not be passed to a third party without prior consent of WJ Horrod Ltd.

WJ Horrod Ltd also reserve the right to alter, change or modify this product to improve it without prior notice.



1 Leaway off Lea Bridge Road London E10 7QW [www.wjhorrod.co.uk](http://www.wjhorrod.co.uk)

©W J Horrod Ltd 2022