



S p e c i f i c a t i o n

Product:	Chute loading anti-splash bolt-on fixed lid Bitumen Boiler	
Model:	SMS4	
Capacity:	25 & 50 Gallon.	
Mounted On:	Free Standing on case sub frame.	
Outside Case:	16-gauge sheet double skin, Rockwool high temperature dense slab insulation between inner and outer skin, profiled end plates and fully welded seams.	
Case Sub Frame:	50 x 25 x 16-gauge ERW 40 x 40 x 3mm RSA	
Removable Pan:	3mm hot rolled sheet fully welded both inside and out.	
Lid:	Fixed (bolted down) anti-splash type with loading chute	
Burner:	Stainless steel ribbon bar burner c/w pilot.	
Thermostat:	Tempcon 2020 digital thermostat control 12/24V. Flame failure pilot protected main burner via flame failure valve.	
Outlet:	1" plug cock type	
Firing:	LPG propane gas.	
Dimensions:	25 gallons;	
	Overall length	1340mm
	Overall width	670mm
	Overall height	990mm
	Weight	145kg approx.
Dimensions:	50 gallons;	
	Overall length	1460mm
	Overall width	770mm
	Overall height	1070mm
	Weight	160kg approx.



This specification and any drawings/images related to it are the sole copyright of WJ Horrod Ltd and must not be passed to a third party without prior consent of WJ Horrod Ltd.

WJ Horrod Ltd also reserve the right to alter, change or modify this product to improve it without prior notice

