



S p e c i f i c a t i o n

Product:	Chute loading anti-splash bolt-on fixed lid Bitumen Boiler
Model:	SMS4
Capacity:	25 & 50 Gallon.
Mounted On:	Free Standing on case sub frame.
Outside Case:	16-gauge sheet double skin, Rockwool high temperature dense slab insulation between inner and outer skin, profiled end plates and fully welded seams.
Case Sub Frame:	50 x 25 x 16-gauge ERW 40 x 40 x 3mm RSA
Removable Pan:	3mm hot rolled sheet fully welded both inside and out.
Lid:	Fixed (bolted down) anti-splash type with loading chute
Burner:	Stainless steel ribbon bar burner c/w pilot.
Thermostat:	Tempcon 2020 digital thermostat control 12/24V. Flame failure pilot protected main burner via flame failure valve.
Outlet:	1" plug cock type
Firing:	LPG propane gas.

This specification and any drawings/images related to it are the sole copyright of WJ Horrod Ltd and must not be passed to a third party without prior consent of WJ Horrod Ltd. WJ Horrod Ltd also reserve the right to alter, change or modify this product to improve it without prior notice.

 72 Years of Excellence
Horrods
Engineering ~ Safety ~ Efficiency



1 Leaway off Lea Bridge Road London E10 7QW www.wjhorrod.co.uk

©W J Horrod Ltd 2022