



## S p e c i f i c a t i o n

Product:	Chute loading anti-splash bolt-on fixed lid Bitumen Boiler
Model:	SMS4
Capacity:	25 & 50 Gallon.
Mounted On:	Free Standing on case sub frame.
Outside Case:	16-gauge sheet double skin, Rockwool high temperature dense slab insulation between inner and outer skin, profiled end plates and fully welded seams.
Case Sub Frame:	50 x 25 x 16-gauge ERW 40 x 40 x 3mm RSA
Removable Pan:	3mm hot rolled sheet fully welded both inside and out.
Lid:	Fixed (bolted down) anti-splash type with loading chute
Burner:	Stainless steel ribbon bar burner c/w pilot.
Thermostat:	Tempcon 2020 digital thermostat control 12/24V. Flame failure pilot protected main burner via flame failure valve.
Outlet:	1" plug cock type
Firing:	LPG propane gas.

This specification and any drawings/images related to it are the sole copyright of WJ Horrod Ltd and must not be passed to a third party without prior consent of WJ Horrod Ltd. WJ Horrod Ltd also reserve the right to alter, change or modify this product to improve it without prior notice.



[www.wjhorrod.co.uk](http://www.wjhorrod.co.uk)

1 Leaway off Lea Bridge Road Leyton London E10 7QW T: 020 8539 8746 Email: [kim@wjhorrod.co.uk](mailto:kim@wjhorrod.co.uk)

Company registered in England No. 682155



[www.wjhorrod.co.uk](http://www.wjhorrod.co.uk)

1 Leaway off Lea Bridge Road Leyton London E10 7QW T: 020 8539 8746 Email: kim@wjhorrod.co.uk

Company registered in England No. 682155