



S p e c i f i c a t i o n

- Product: Thermostat Control Bitumen Boiler
- Model: SMS2
- Capacity: 25 & 50 Gallon.
- Mounted On: Sub-frame fitted with 2 No. 12" solid rubber tyre wheels
- Outside Case: 16-gauge sheet double skin, Rockwool high temperature dense slab insulation between inner and outer skin, profiled end plates and fully welded seams.
- Case Sub Frame: 50 x 25 x 16-gauge ERW
40 x 40 x 3mm RSA
- Removable Pan: 3mm hot rolled sheet fully welded both inside and out.
- Lid: Full size fully opening
- Burner: Stainless steel ribbon bar burner c/w pilot.
- Thermostat: Tempcon 2020 digital thermostat control 12/24V. Flame failure pilot protected main burner via flame failure valve.
- Outlet: 1" Plug cock type – Gate Type
- Firing: LPG propane gas.

Dimensions:	25 gallons:	50 gallons:
Overall length	1420mm	Overall length 1620mm
Overall width	670mm	Overall width 770mm
Overall height	840mm	Overall height 945mm
Weight	160kg approx.	Weight 180kg approx.



This specification and any drawings/images related to it are the sole copyright of WJ Horrod Ltd and must not be passed to a third party without prior consent of WJ Horrod Ltd.

WJ Horrod Ltd also reserve the right to alter, change or modify this product to improve it without prior notice.



1 Leaway off Lea Bridge Road London E10 7QW www.wjhorrod.co.uk

©W J Horrod Ltd 2024