

S p e c i f i c a t i o n

Product: Trailer Mounted Thermostat Control Bitumen Boiler.

Model: SMS5

Capacity: 50 Gallon.

Boiler Specification:

Outside Case: 16 gauge hot rolled sheet double skin, Rockwool high temperature dense slab

insulation between inner and outer skins, seams fully welded.

Case Sub Frame: 50 x 25 x 2.5 RHS

40 x 40 x 3mm RSA

Removable Pan: 3mm hot rolled sheet fully welded both inside and out.

Lid: Fixed (bolt down) anti-splash type with loading chute.

Burner: Stainless steel ribbon bar burner c/w with pilot.

Thermostat: Tempcon 2020 digital thermostat control 12/24V. Flame failure pilot protected main

burner via flame failure valve.

Material Outlet: 1" plug cock type.

Firing: LPG propane gas.



Trailer Specification:

Type: Unbraked.

Chassis:

Main Chassis: 80 x 40 x 4 RHS.

Main Suspension: Un-braked 750kg unit.

Wheels: 4 Stud 5½" PCD wheels fitted with 165 R 13 8PR 96N tyres.

Mudguard: Steel 13"

Tow Couple: Option of tow eye or ball head.

Jockey Wheel: 42mm smooth jockey wheel assembly.

Trailer Lights: Radex rear lamp 5 function plug in left – Radex rear lamp plug in c/w number plate

lamp – c/w 7 pin plug – Independent red triangle reflectors.

Finish: Colour of your choice – subject to colour – one coat Selemix.

Please be advised Highways yellow required 3 coats and there is an additional charge

for this.

Approx Sizes: Length: 3000mm (50 Gallon SMS4)

Width: 14650mm

Height: 1600mm (dependent on lid type)
Weight: 340kg (dependent on lid type)

This specification and any drawings/images related to it are the sole copyright of W.J. Horrod Ltd and must not be passed to a third party without prior consent of W.J. Horrod Ltd.

WJ Horrod also reserve the right to alter, change or modify this product to improve it without prior notice.



