



S p e c i f i c a t i o n

Product:	Trailer Mounted Thermostat Control Bitumen Boiler.
Model:	SMS5
Capacity:	50 Gallon.
<u>Boiler Specification:</u>	
Outside Case:	16 gauge hot rolled sheet double skin, Rockwool high temperature dense slab insulation between inner and outer skins, seams fully welded.
Case Sub Frame:	50 x 25 x 2.5 RHS 40 x 40 x 3mm RSA
Removable Pan:	3mm hot rolled sheet fully welded both inside and out.
Lid:	Fixed (bolt down) anti-splash type with loading chute.
Burner:	Stainless steel ribbon bar burner c/w with pilot.
Thermostat:	Tempcon 2020 digital thermostat control 12/24V. Flame failure pilot protected main burner via flame failure valve.
Material Outlet:	1" plug cock type.
Firing:	LPG propane gas.



T r a i l e r S p e c i f i c a t i o n :

Type:	Unbraked.		
<u>Chassis:</u>			
Main Chassis:	80 x 40 x 4 RHS.		
Main Suspension:	Un-braked 750kg unit.		
Wheels:	4 Stud 5½" PCD wheels fitted with 165 R 13 8PR 96N tyres.		
Mudguard:	Steel 13"		
Tow Couple:	Option of tow eye or ball head.		
Jockey Wheel:	42mm smooth jockey wheel assembly.		
Trailer Lights:	Radex rear lamp 5 function plug in left – Radex rear lamp plug in c/w number plate lamp – c/w 7 pin plug – Independent red triangle reflectors.		
Finish:	Colour of your choice – subject to colour – one coat Selemix. Please be advised Highways yellow required 3 coats and there is an additional charge for this.		
Approx Sizes:	Length:	3000mm	(50 Gallon SMS4)
	Width:	14650mm	
	Height:	1600mm	(dependent on lid type)
	Weight:	340kg	(dependent on lid type)

This specification and any drawings/images related to it are the sole copyright of W.J. Horrod Ltd and must not be passed to a third party without prior consent of W.J. Horrod Ltd.

WJ Horrod also reserve the right to alter, change or modify this product to improve it without prior notice.



74 Years of Excellence
Horrods
Engineering ~ Safety ~ Efficiency



1 Leaway off Lea Bridge Road London E10 7QW www.wjhorrod.co.uk

©W J Horrod Ltd 2023